Trimble TDC600

HANDHELD



KEY FEATURES

- ► All-in-one GNSS data collector and smartphone
- ► Android[™] 10 operating system

- ► 6-inch high resolution sunlight-readable display
- Powerful Qualcomm® processor with 4 GB RAM and 64 GB internal storage
- ► Large capacity, user replaceable all day battery
- Real-time positioning with built-in GNSS receiver
- Google Mobile Services certified with access to Google Play™ store apps
- Ultra-rugged design with MIL-STD-810G certification
- 4G LTE, Wi-Fi, Bluetooth® connectivity options for voice calls and data
- ► Ergonomic, lightweight and slim form factor
- Front- and rear-facing cameras
- Supports the Trimble[®] Catalyst[™] and Trimble R Series GNSS receivers
- Runs Trimble TerraFlex®, Trimble Access™, third-party or custom-developed field applications

Learn more: geospatial.trimble.com/tdc600



Trimble TDC600 HANDHELD

++++++++++++++++

...... 196 mm x 93.4 mm x 17.2 mm (7.7 in x 3.6 in x 0.67 in)

++++++++++++

STANDARD FEATURES

SYSTEM

- Integrated 4G cellular data, text and voice capability
 5 MP front camera and 13 MP rear camera
- Bluetooth v 4.1
- Wi-Fi IEEE 802.11 a/b/g/n/ac, 2.4 GHz / 5 GHz dual-band
- 6.0 inch LED-backlight screen with capacitive multi-touch
- · Long-life user replaceable Li-lon battery
- 2.2 GHz Qualcomm Snapdragon™ 626 processor
- 4 GB RAM
- 64 GB flash memory¹
- · 1 MicroSDHC memory card slot
- · Integrated speaker and microphone

OPERATING SYSTEM

- · Android 10
- · Languages available: Afrikaans, Azebaijani, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hindi, Hungarian, Italian, Korean, Lithuanian, Norwegian (Bokmål), Polish, Portuguese (Portugal and Brazil), Romanian, Russian, Serbian (Cyrillic), Simplified Chinese, Spanish, Swedish, Turkish
- Software package includes: Google Mobile Services
- · Android Security Updates provided until December 2024

COMMUNICATIONS²

- Cellular: GSM (850/900/1800/1900), WCDMA (B1/B2/B5/B8), LTE-FDD (B1/ B2/B3/B4/B5/B7/B8/B12/B13/B17/B20/B25/B28), LTE-TDD (B38/B39/B40/ B41), TD-SCDMA (B34/B39)
- Wi-Fi IEEE 802.11 a/b/g/n/ac
- Bluetooth 4.1
- NanoSIM x 2
- USB 3.0 (Type-C)
- NFC (13.56 MHz)

STANDARD ACCESSORIES

- · Hand strap
- A/C charger
- USB cable
- Lanyard

OPTIONAL ACCESSORIES

- External magnetic GPS antenna
- Pole bracket
- Replacement batteries
- Dual battery charger

SOFTWARE COMPATIBILITY

Please refer to the Product Compatibility matrix. (www.trimble.com/mappingGIS/productcompatibility)

TECHNICAL SPECIFICATIONS

PHYSICAL

Size...

ENVIRONMENTAL

0 °C to +55 °C (-4 °F to +131 °F)
10 °C to 70 °C (-40 °F to 158 °F)
95% non-condensing
IP67
1.2 m (3.9 ft) (MIL-STD-810G)

INPUT/OUTPUT

Expansion	MicroSDHC memory card (up to 256 GB)
Display	Gorilla Glass 3, Optically bonded, AF coated, auto rotate
Size	6.0" capacitive multi-touch
Resolution	1920 x 1080 pixels
Brightness	
Audio	Built-in microphone and speaker
	Audio jack through USB-C
	Pogo pin connector
I/O	USB 3.0, external antenna connector
Digital camera	
Rear camera	
Front camera	5 MP with fixed focus
Sensors	

GNSS

GNSS Receiver	U-blox Neo-M8T
Internal antenna: 72 channels	GPS L1 C/A, GLONASS, BeiDou, SBAS
Integrated real-time	SBAS (WAAS/EGNOS/MSAS/GAGAN/QZSS)
Tri constellation system	GPS/GAL, GPS/GLO/GAL or GPS/BeiDou/GAL
External antenna connector	Yes
Protocol	Location Services
	NMEA output (optional)

ACCURACY SPECIFICATIONS (HORIZONTAL RMS)3

Real-time SBAS⁴.....<1.5 m (4.9 ft) typical

- 1 The actual available capacity of the internal memory is less than the specified capacity because the operating system and default applications occupy part of the memory. The available capacity may change when you upgrade applications or the device.
- Bluetooth, wireless LAN and cellular type approvals are country specific. Trimble TDC600 handheld has Bluetooth, wireless LAN and cellular approval in North America and EU. For other countries, please consult your local Distributor.
- your local Distributor.

 3 Horizontal Root Mean Squared accuracy. Requires data to be collected using vertical mounting, minimum of 4 satellites, PDOP mask at 99, SNR mask at 12 dBHz, elevation mask at 5 degrees, and reasonable multipath conditions. Inonspheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception.

 4 SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only, EGNOS (European Geostationary Navigation Overlay System) available in Europe only, and MSAS available in Japan only.

Specifications subject to change without notice

C ∈ Bluetooth

Contact your local Trimble Authorized Distribution Partner for more information

NORTH AMERICA

Trimble Inc. 10368 Westmoor Dr Westminster CO 80021 **FUROPE**

Trimble Germany GmbH Am Prime Parc 11 65479 Raunheim GERMANY

ASIA-PACIFIC

Trimble Navigation Singapore PTE Limited 3 HarbourFront Place #13-02 HarbourFront Tower Two Singapore 099254 SINGAPORE

© 2019–2023. Trimble Inc. All rights reserved. Trimble, and the Globe & Triangle logo, and TerraFlex are trademarks of Trimble Inc., registered in the United States and in other countries. Access and Catalyst are trademarks of frimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. Google, Google Play, Android e outras marcas são marcas comerciais da Google LLC. All other trademarks are the property of their respective owners. PN 022516-439G (08/23)

